

Operating Instructions for "Kabi"

- 1 Obtain keys from Bar to access Top Shed
- 2 Ensure the roller door is completely open or the canopy of Kabi will hit it.
- 3 Check fuel tanks to ensure you have enough for the days work.
- 4 Turn ON power isolation switch (located inside of console on starboard side)
- 5 Ensure drain bungs are in. (located plastic container on starboard side of motor)
- 6 Raise motor before moving trailer.
- 7 Connect trailer to vehicle then erect canopy.
- 8 Ensure you have correct buoys and they are inflated.
- 9 Wind boat off trailer using winch handle, do not let it spin madly as injury can occur if it hits you.
- 10 Squeeze fuel line pressure bowl until hard before starting motor by turning key (do not use choke lever, all motors have auto choke)
- 11 Allow motor to warm for 30 seconds before proceeding.
- 12 Turn on GPS - (refer to GPS instructions) (nb. Track on GPS is only accurate when moving)
- 13 Proceed to suitable location and take wind readings (allow 20 -30 mins for this).
- 14 Do radio check with Base and Jean
- 15 Use Wind direction plotter sheet in folder under console decide on average wind direction and in conjunction with the protractor ascertain bearings to marks and back bearings.
- 16 Confirm wind direction with crew on Jean then proceed to start area to set line. (Drop start mark over starboard side and slowly tow with anchor until ready to drop).
- 17 Set GPS Man overboard (MOB) while alongside Mark 3 (Refer GPS instructions)
- 18 Proceed to windward dropping Mark 1 at agreed distance from Mark 3. (Check that your back bearing on GPS to MOB is correct before dropping mark).
- 19 Using hand bearing compass select a landmark to steer to for Mark 2. Proceed on this heading until bearing on GPS to MOB is the required bearing to Mark 3.
* Double check the bearing back to Mark 1 is correct before dropping Mark 2
- 20 Proceed towards Mark 3 until bearing to Mark A is correct then drop Mark B
- 21 After last start drop finish mark to leeward of Start Boat.
- 22 Monitor fleet for any assistance required.

Retrieving Kabi from water.

- 1 Proceed carefully back to boat ramp.
- 2 Remember to raise motor before entering shallow water.
- 3 Ensure boat is straight on trailer before winching.
- 4 Return to Top Shed to wash and flush motor. Drop canopy, aerial etc.
Raise motor before unhooking from tow vehicle.
- 5 Replace Top Shed keys back in Bar.

Well done, and thank you.

If you have any queries please ask for assistance during the morning that you are rostered.